



date tehnice

separatoare ciclon de condens BOGE Z

model	capacitate / debit vehiculat			racord	dimensiuni		greutate ca.
	m ³ /min				mm		
	8 bar	10 bar	13 bar	intr / iesi	D	H	kg
Z 20N	2,20	2,80	3,50	1/2"	103	238	1,50
Z 35N	3,85	4,90	6,13	3/4"	139	324	1,70
Z 53N	5,87	7,47	9,33	1"	139	324	3,50
Z 75N	8,25	10,50	13,13	1 1/2"	190	528	4,50
Z 125N	13,75	17,50	21,88	2"	190	528	5,90
Z 183N	20,17	25,67	32,08	2"	190	528	8,50
Z 275	30,25	38,50	48,13	2 1/2"	180	580	15,40
Z 375	41,25	52,92	65,63	3"	180	580	18,70

separatoarele ciclon **BOGE, Z**, se livreaza cu carcasa de aluminiu fara purja automata interna / extrena, purja se alege separat

OPTIUNI

purja automata externa cu plutitor	AOK20B
purja automata cu temporizare	TD/MD
purja automata electronica BEKO	Beko

debit aer comprimat vehiculat se refera la free air delivery FAD la 20 grdC, 7 bar
presiunea maxima aer comprimat 16 bar (g) ptr. separator ciclon
specificatii tehnice conform clasa de calitate ISO8573-1