

**VASE REZERVOR pentru AER COMPRIMAT 42, 48 bar****Mediu de lucru acceptat:****grupa de fluid 1** Aer comprimat/Azot/Argon//Heliu/Apa/Ulei fara O₂ si H₂ si **grupa de fluid 2****Produce conform** 2014/68/UE PED (ex. CE97/23 PED) cu marca, **CE**, declaratie de conformitate, desen de executie, carte tehnica, traduceri aferente**Pregatirea suprafetei:** sablat pe exterior, vopsit in camp electrostatic sau lichid (cele peste 3000 l) sau galvanizat la cald interior exterior.**Varianta constructiva:** vertical pe 3 picioare**Temperatura** de functionare standard: -10 ÷ + 50 °C**Gura vizitare mana PM 100x150 mm:** standard la vasele de 500 l (1buc) 1000 – 3000 l (2 buc)**Gura vizitare om PU 320x420 mm:** standard la vasele de 4000 – 5000 l**Date tehnice vase rezervor verticale pentru aer comprimat 42 bar:**

Tip vas * l	P _{de lucru} ** bar	Diametru exterior mm	H _{total} mm	Inaltime purjare mm	Racord sus/jos “	Racord lateral “	Racord frontal “	Greutate ca. kg
500	42,00	600	2140	190	2	2	3/4&3/8	340
1000	42,00	790	2385	200	2	2	3/4&3/8	605
1500	42,00	950	2470	185	2	2	3/4&3/8	755
2000	42,00	1000	2810	175	2	2	3/4&3/8	1025
3000	42,00	1200	2970	170	2	2	3/4&3/8	1450
4000	42,00	1430	3160	190	2	2	3/4&3/8	2190
5000	42,00	1430	3660	190	2	2	3/4&3/8	2515

Date tehnice vase rezervor verticale pentru aer comprimat 48 bar:

Tip vas * l	P _{de lucru} ** bar	Diametru exterior mm	H _{total} mm	Inaltime purjare mm	Racord sus/jos “	Racord lateral “	Racord frontal “	Greutate ca. kg
1000	48,00	790	2385	200	2	2	3/4&3/8	725
1500	48,00	950	2470	185	2	2	3/4&3/8	850
2000	48,00	1000	2810	175	2	2	3/4&3/8	1195
3000	48,00	1200	2970	170	2	2	3/4&3/8	1685

Optional:

vasele pot fi tratate in interior cu vopsea speciala VITROFLEX la cererea beneficiarului
se livreaza: **seturi de reductii, dopuri**, racorduri pentru fiecare vas in parte
montaj al vaselor rezervor la pozitie si la cerinta beneficiarului